

**STANDARDS PRESENTATION  
TO  
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD**

PROPOSED STATE STANDARD,  
TITLE 8, DIVISION 1, CHAPTER 4

Amend Section 1598 to read:

§1598. Traffic Control for Public Streets and Highways.

(a) Where a hazard exists to employees because of traffic or haulage conditions at work sites that encroach upon public streets or highways, a system of traffic controls in conformance with the "California Manual on Uniform Traffic Control Devices for Streets and Highways, September 26, 2006," which is herein incorporated by reference and referred to as the "Manual", published by the State Department of Transportation, shall be required so as to abate the hazard.

NOTE: Additional means of traffic control, such as continuous patrol, detours, barricades, or other techniques for the safety of employees may be employed.

(b) Specifications for the size and design of signs, lights, and devices used for traffic control shall be as described in the "Manual", pursuant to the provisions of California Vehicle Code Section 21400, which is incorporated by this reference.

(c) Employees (on foot) exposed to the hazard of vehicular traffic shall wear ~~orange, strong yellow-green, or fluorescent versions of these colored~~ warning garments such as vests, jackets, or shirts in accordance with the requirements of the American National Standards Institute (ANSI)/International Safety Equipment Association (ISEA) 107-2004, High Visibility Safety Apparel and Headwear, Sections 1 – 12 and Appendices B and C, which are hereby incorporated by reference. ~~During rainy weather, employees exposed to the hazard of vehicular traffic may wear orange, strong yellow-green, or yellow rainwear.~~

(d) During hours of darkness, warning garments shall be retroreflective in accordance with the requirements of the American National Standards Institute (ANSI)/International Safety Equipment Association (ISEA) 107-2004, High Visibility Safety Apparel and Headwear, Sections 4 – 9.4.8 and Appendices A – C, which are hereby incorporated by reference. The retroreflective material shall be visible at a minimum of 1,000 feet. ~~The retroreflective clothing, or the retroreflective material added to the clothing, shall have a minimum of one horizontal stripe around the torso.~~ White outer garments with retroreflective material that meets the above requirements may be worn during hours of darkness but not during snow or fog conditions, in lieu of colored vests, jackets and/or shirts.

NOTE: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.

**STANDARDS PRESENTATION  
TO  
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD**

PROPOSED STATE STANDARD,  
TITLE 8, DIVISION 1, CHAPTER 4

Amend Section 1599 to read:

§1599. Flaggers.

(a) Flaggers shall be utilized at locations on a construction site where barricades and warning signs cannot control the moving traffic.

(b) When flaggers are required, they shall be placed in relation to the equipment or operation so as to give effective warning.

(c) Placement of warning signs shall be according to the California Manual on Uniform Traffic Control Devices for Streets and Highways, September 26, 2006, published by the State Department of Transportation, which is herein incorporated by reference and referred to as the "Manual."

(d) Flaggers shall wear ~~orange, strong yellow-green, or fluorescent versions of these colored~~ warning garments such as vests, jackets, or shirts in accordance with the requirements of the American National Standards Institute (ANSI)/International Safety Equipment Association (ISEA) 107-2004, High Visibility Safety Apparel and Headwear, Sections 1 – 12 and Appendices B and C, which are hereby incorporated by reference. ~~Rainwear, when worn, shall be orange, strong yellow-green, or yellow.~~

(e) During the hours of darkness, flaggers' stations shall be illuminated such that the flagger will be clearly visible to approaching traffic and flaggers shall be outfitted with reflectorized garments in accordance with the requirements of the American National Standards Institute (ANSI)/International Safety Equipment Association (ISEA) 107-2004, High Visibility Safety Apparel and Headwear, Sections 4 – 9.4.8 and Appendices A – C, which are hereby incorporated by reference. The retroreflective material shall be visible at a minimum distance of 1,000 feet. ~~The retroreflective clothing, or the retroreflective material added to the clothing, shall have a minimum of one horizontal stripe around the torso.~~ White outer garments with retroreflective material that meets the above requirements may be worn during hours of darkness but not during snow or fog conditions, in lieu of colored vests, jackets and/or shirts.

\*\*\*\*\*

NOTE: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.